

METAL PLATE EMBOSSING SYSTEM



C410



FASTER & EASIER TO USE

The C410 electronic embosser is the next generation of the well known C400. With speeds of up to 350 plates per hour, it is 45% faster than before. A new cover design allows easier operator access and ruggedly built to withstand the harshest industrial environments.

Specifically engineered for heavy duty and continuous production, the C410 is the strong, reliable system ready to emboss plates and can handle a huge variety of sizes, materials, shapes and thicknesses.

METAL PLATE EMBOSSING SYSTEM



AUTOMATIC UNIVERSAL FEED

The C410 comes equipped with an integrated, manually adjustable universal automatic plate feeder that can hold up to 350 plates (0.50 mm. thickness), the C410 is particularly suited for continuous medium- to high-volume production process.



Through the manually adjustable plate feeding mechanism, the C410 can easily accommodate plates of varying sizes and shapes and efficiently can be used to emboss different identification plates within the same production facility.

Once embossed, plates can either be placed in an external collection box through a side eject mechanism or stacked in a FIFO output stacker, offered as an option.

HEAVY DUTY EMBOSSING MECHANISM

The C410 is equipped with a heavy duty embossing mechanism which includes a powerful high torque motor, high percussion embossing arms, hardened drum and special hardened fonts to tackle the hardest jobs.




The C410 is designed to personalize plates of various materials and thicknesses including steel, iron, aluminium, bronze and more with a result that meets the highest standards of quality.

A LARGE VARIETY OF EMBOSSING WHEELS AND FONT SIZES AVAILABLE

To accommodate the many different requirements across industries, the C410 can be equipped with a large variety of embossing wheels and font styles. Embossing drum capacity ranges from 60 to 100 characters slots, and special drums are available for the automotive industry to accommodate specially designed fonts and dual sets of fonts. Standard font sizes range from 3 mm. to 12 mm. in height and most are available in embossing and indent. Special fonts and logos can be manufactured upon request.

SIDE-EJECT OR FIFO OUTPUT STACKER

The C410 is also equipped with a side-eject system with an external plate collection tray. This is particularly suited for those jobs where plate sizes and shapes frequently change.



However, for larger volumes of a specified plate size, an optional FIFO stacker elevator mechanism is available. This option includes a time saving sensor which prevents machine operation when the FIFO stacker is full of embossed plates.

MATICARD PRODUCTION SOFTWARE


The C410 runs on Maticard®, Matica's innovative software that runs every Matica machine with a single program. Easy to use and easy to install, no longer do you have to suffer through multiple installations of software. One training is all you need, regardless of the type of the machine purchased.

ON-LINE OR OFF-LINE

Data can be entered through a keyboard in an off-line mode, using the LCD display to view the information being typed. Thanks to the LAN connection (option) and to the RS232 port, the system can also be easily connected as a common office printer and operate online with a PC or host computer. An external LCD display provides the operator with continuous machine status and allows real time monitoring of the plate personalisation process.

MANUAL FEED

C410 MF is a new version of C410 metal embosser created for special need and for product customization. The metal plate is loaded and, after the embossing, removed manually from the Clamp on the C410 MF.



Technical features

Productivity (40 ch/plate):

- Up to 350 plates/hour

Plate handling:

- Input hopper capacity: 350 plates (0.5 mm thickness)
- Input hopper height: 185 mm
- Side eject or optional automatic variable FIFO elevator
- Plate thickness from 0.4 to 0.9 mm

Plate personalization:

- Minimum plate dimensions (WxD): 50 mm x 20 mm
- Maximum plate dimensions (WxD): 120 mm x 90 mm
- Maximum embossing area (WxD): 120 mm x 80 mm
- Minimum embossing area (wxD): 30 mm x 16 mm
- Non embossing area: 4mm from the bottom of the plate

Embossing Drum Configuration:

- Embossing drum: 60 or 100 characters (special drums available upon request)
- Major available type (alphanumeric):
 - Simplex 2 (350) - 3mm
 - Blocco USA (490) - 4mm
 - Blocco (488) - 5mm
 - Doppio Blocco (511) - 6mm (50 characters drum)
 - Doppio Blocco Lungo (611) - 8mm (50 characters drum)
 - Maxi Blocco (711) - 12mm (50 characters drum)

Communication interface:

- RS232 serial port
- LAN - Ethernet (option)
- Protocol: Xon/Xoff; Pound Pound, Multiembosser, Euro2, SEP

Other Features:

- Key-lock security feature
- LCD Display (40 x 2) + 3 function keys
- PC keyboard
- Upgradeable Firmware: Via PC on Flash EPROM
- Maticard® Design Software (Windows® XP/2K)
- Diagnostics and Set-up software

Dimensions:

- Width: 91 cm
- Depth: 60 cm
- Height: 42 cm

Weight: 70 Kg

Power Requirements:

- Electrical requirements: 100V ~ 240V 50/60Hz (auto sensing)

All trademarks stated are the property of their respective owners. V. 1.6
Data subject to change without notice